

## ORDERING EXAMPLE

PLG 40-80-DP HT

### PLG

#### GRIPPER

- **PLG**

### 40-80-DP

#### VERSION

##### Standard

- **25-40** = size 25, stroke 40 for jaw
- **25-60** = size 25, stroke 60 for jaw
- **40-60** = size 40, stroke 60 for jaw
- **40-80** = size 40, stroke 80 for jaw
- **40-100** = size 40, stroke 100 for jaw
- **60-60** = size 60, stroke 60 for jaw
- **60-100** = size 60, stroke 100 for jaw
- **60-200** = size 60, stroke 200 for jaw

##### With device to maintenance the gripping force

- **25-30-MC** = size 25, stroke 30 for jaw
- **40-40-MC** = size 40, stroke 40 for jaw
- **60-50-MC** = size 60, stroke 50 for jaw

##### With dust protection IP64

- **25-60-DP** = size 25, stroke 60 for jaw
- **40-80-DP** = size 40, stroke 80 for jaw
- **60-100-DP** = size 60, stroke 100 for jaw

##### With device to maintenance the gripping force and dust protection

- **25-30-MC-DP** = size 25, stroke 30 for jaw
- **40-40-MC-DP** = size 40, stroke 40 for jaw
- **60-50-MC-DP** = size 60, stroke 50 for jaw

### HT

#### VARIANTS (possible combinations)

- **HT** = Version up to 130°C

#### STROKE CONTROL (preparation, excluded sensors)

*C-Slot included for R626 or R793 magnetic sensor, do not indicate codes*

- **B8** = Settable kit for M8x1 inductive sensor application

#### OPTIONAL

- **CS** = Induktive sensor
- **CM** = Magnetic sensor
- **TY** = Quick-change Jaw System
- **JUS** = Universal intermediate jaw, to adjust the position
- **VMP** = Pressure maintenance valve
- **MPS** = Magnetic position sensor SICK (solution to control the entire stroke)