

ORDERING EXAMPLE

PZP 100 C1 MC DP B8 P GS

PZP

GRIPPER

- **PZP**

100

SIZE

- 40 | 50 | 64 | 80 | **100** | 125 | 160 | 200 | 240 | 300

C1

VERSION

- **C1** = Long stroke
- **C2** = Short stroke, greater gripping force

MC

DEVICE TO MAINTENANCE THE GRIPPING FORCE

(for version without device do not indicate codes)

- **MC** = Normally closed, in case of lack of air the gripper closes
- **MA** = Normally open, in case of lack of air the gripper opens

DP

VARIANTS *(possible combinations)*

- **DP** = Dust-protection version IP 64
- **TDM** = Force intensified version, max size 200, combined MC/MA only in C1
- **HP** = Precision version +/-0.025
- **HT** = Version up to 130°C
- **AC** = Anti-corrosion version
- **TS** = version with T-slot for SICK multiple position sensor

B8

STROKE CONTROL *(preparation, excluded sensors)*

C-Slot included for R626 or R793 magnetic sensor, do not indicate codes

- **B5** = Settable kit for M5 inductive sensor application (size 64)
- **B8** = Settable kit for M8x1 inductive sensor application (sizes 80...300)

P

GS

OPTIONAL

- **P** = Pressure plate
- **CS** = Inductive sensor
- **CM** = Magnetic sensor
- **TS** = SICK multiple position sensor
- **TY** = Quick-change Jaw System
- **JUS** = Universal intermediate jaw, to adjust the position
- **GS** = Top jaw blank, steel GS-CC, aluminium GS-LL
- **VMP** = Pressure maintenance valve